

ERF 104

FLOOR PLAN / GROUND FLOOR
SCALE 1:50

ERF 103

ERF 105
J-BAY
732.11 sqm

ELECTRICAL LEGEND

- Single wall mounted light switch to be mounted at 1300mm above ufl.
- Double wall mounted light switch to be mounted at 1300mm above ufl.
- Triple wall mounted light switch to be mounted at 1300mm above ufl.
- 2-way wall mounted light switch to be mounted at 1300mm above ufl.
- Waterlight wall mounted light switch to be mounted at 1300mm above ufl.
- Dimmer wall mounted light switch to be mounted at 1300mm above ufl.
- Double wall mounted plug, top of socket to be 125mm above ufl.
- Double wall mounted plug, top of socket to be 300mm above ufl.
- Double wall mounted watertight plug
- Extractor connection plug @ 2100mm
- Blank conduiting boxes
- Periscope plug as per specification.
- Garage door ceiling mounted motor
- TV point aerial
- Shavers plug
- Tekom point
- Network point
- Stove isolator
- Power Skirting
- (2 x 18 W) 1500 Long 2 tube fluorescent armature with external wall mounted suspended from ceiling.
- 5 Watt LED Down lighter as per specification
- 20 Watt Compact Fluorescent hanging pendant light as per specification
- 20 Watt Compact Fluorescent ceiling light as per specification
- 30 Watt Fan-light ceiling mounted
- (5 Watt x 2) Internal LED Wall mounted light
- (10 Watt x 2) External LED Wall mounted light
- 50 Watt External LED Wall mounted spotlight
- 13 Watt Internal compact Fluorescent up lighter (wall mounted) as per client
- Stairlights (wall mounted) as per client
- LED Strip Lighting
- Pool light as per client
- Foot light
- Electrical fence control box.
- Gate Control Unit
- Pre-paid Electricity meter
- Daylight sensor
- Intercom panel
- Intercom system
- Alarm panel
- Alarm system
- Hot dryer waterproof plug
- Main distribution board
- Sub distribution board
- Uninterruptible power supply
- Sleeve to be installed for future Fibre optic installations, sleeve to be as per specialist.

WATER RETICULATION LEGEND

- proposed cold water source point, plumber to top into existing cold water pipes of this point
- garden tap position
- proposed cold water reticulation
- proposed hot water reticulation
- proposed cold water pipe up
- proposed cold water pipe down
- proposed hot water pipe down
- proposed cold water stopcock
- proposed hot water stopcock
- proposed cold tap
- proposed hot tap
- shower head
- external mounted heat pump as per specialist.
- solar geyser on roof with geyser in the ceiling space as per specialist.
- 95mm flexible polyester Borelet insulation to new geyser to achieve R-value of 2.00
- 50mm flexible polyester insulation to all new hot water pipes to achieve R-value of 1

FIRE PLAN LEGEND

- Smoke Detectors
- Manual Control Panel
- Signage for direction of fire escape route
- Signage for fire extinguisher
- Fire extinguisher
- Fire blanket
- Fire escape route
- 30m Fire hose reel
- Fire hydrant
- 30m FHR

KOUGA MUNICIPALITY
Building Control Department
Conditionally Approved/Voorwaardelik Goedgekeur

PLAN NR
J2425-01421

AESTHETICS COMMITTEE:

BUILDING CONTROL OFFICER:

APPROVING OFFICER:

DATE: Building 13 Aug 2025

Plans are valid for 12 months
Section 7(4) NBR

REVISIONS:

REV01-01	New trough and new generator position	2025-07-09
REV01-02	New concrete platform and balustrade	2025-07-09
REV01-03	Door and window changed	2025-07-09
REV01-04	New reception area with sliding doors	2025-07-09
REV01-05	Changed to only one unisex toilet.	2025-07-09
REV01-06	New steps added	2025-07-09

GENERAL NOTES:

All dimensions to be checked on site before construction commences. All dimensions are given in millimeters, unless otherwise specified. Contractors to adhere to all local authority's regulations and requirements. Contractors to be a suitably qualified and registered participant in the construction industry as required by Construction Regulation 2014. Drawings to be read in conjunction with the client's OHS (Occupational Health and Safety) file. All work to be done in accordance with the National Building Regulations SANS 10400. Before this drawing is priced it is the contractor's responsibility to ensure he is familiar with the site. All trade names quoted may only be substituted by similar, subject to architect's approval. All materials to be installed in strict accordance with manufacturer's specifications. All conduit work to be SABS approved quality. All light fittings to be fitted to comply with the relevant code of practice as specified in SANS 10400: Part C. All new work to be made good with existing. This drawing is not to be scaled unless printed by H. Gouws renders. All existing dimensions not to be scaled from drawings but to be checked on site. Any discrepancies shall be reported to the designer immediately and clarified by the architect prior to commencement of work. Top of foundations to be a minimum of 150mm below finished ground level. Minimum 100mm thick concrete surface bed as per Engineers drawings to be on 250 mic. 'gunplas' ub's green dpm on 50mm sand blinding layer and on well compacted fill in layers not more than 150mm. SABS Approved 'gunder' 375 mic. dpc under all walls, window cills and at changes in floor level. These architectural drawings to be read in conjunction with engineers and consultants drawings, where applicable. All building work to be carried out in accordance with the national building regulations. The contractor is responsible for all site visits by local inspectors and pay all fees in connection therewith. All drainage work to be carried out in accordance with the national building regulations. All roof measurements to be taken on site by roof specialist prior to roof construction. All tile layouts to be confirmed with architect prior to commencing. Levels shown are relative to a benchmark of 100.00 msl of new floor level. Msl is not the actual level but a benchmark to base other heights of the building shown on the drawings. Contractor to keep a full set of latest issued drawings on site. Contractor is responsible for the correct setting out of the building on site with reference to the building line and boundaries. Contractor to take responsibility for all health and safety measures on site.

DRAWING TITLE:

DEVIATION PLAN

PROJECT TITLE:

ADDITIONS AND ALTERATIONS ON ERF 105, JEFFREYS BAY, PORT/ELIZABETH FOR Mr & Mrs Dicks

CLIENT SIGNATURE: 17 Jul 25

BLACKHOUND
ARCHITECTURE & RENDERING

hannes@blackhousedownterprises.com
072 799 5597 | 072 418 6867
http://blackhousedownterprises.com
Unit 10, The Network, 19 Cactus Rd
Fairview, Port Elizabeth, 6070

PROFESSIONAL SIGNATURE: 17 Jul 25

MUNICIPAL INFORMATION:

ERF NO:	105, JEFFREYS BAY
ERF AREA:	732.11 sqm
EXISTING AREA:	522 sqm
NEW AREA:	54 sqm
TOTAL AREA:	576 sqm
EX. COVERAGE:	293 sqm - 40%
NEW COVERAGE:	54 sqm - 7%
TOTAL COVERAGE:	347 sqm - 47%
NEW GARAGES:	0
NEW BATHROOMS:	3
POOL:	NO
BOUNDARY WALLS:	0 M
AGE OF BUILDING:	<60

PROFESSIONAL SENIOR
ARCHITECTURAL TECHNOLOGIST
JOHANNES STEPHANUS GOUWS
17:03 per (Africa/Johannesburg) on 17 Jul 2025

COPYRIGHT:
This drawing is subject to copyright, and may not be reproduced in whole or part in any manner whatsoever without written permission from Blackhound Architecture & Rendering.

PROJECT NO.:	2025, DANIE	REVISION NO.:	01
DRAWING NO.:	20250717_DANIE_MS01	SHEET NO.:	101
DRAWN BY:	DMP		
PRINT DATE:	17 Jul 2025	PAGE SIZE:	A1